


Function	Single acting cylinder - gas spring	
Bore	50	mm
Stroke	500	mm
Pull load @ 350 bar (max pressure)	6288	kg
Pull load @ 250 bar	4491	kg
Pull load @ 200 bar	3593	kg
Approx. dry weight	3,5	kg
Max oil volume	0,53	l

REV.	DATA / DATE	DESCRIZIONE / DESCRIPTION	NOME / NAME
RIFERIMENTO / REFERENCE			TABLE
TRAT. TERMICO / HEAT TREAT.			SIZE
TRAT. SUPERFICIALE / FINISH			A1
CONTROLLATO / CHECKED	DATA / DATE	MATERIALE / MATERIAL	 CARIBONI S.r.l. Via Mattei 3/A 20885 Ronco Briantino e-mail: info@cariboni-italy.it www.cariboni-italy.com Tel +39 039 6079609 fax +39 039 6079128
AC	30-11-2017		
APPROVATO / APPROVED	DATA / DATE	SCALA / SCALE	
1:3@A1		PESO/ WEIGHT kg	
DISSEGNO N. / DRAWING	REV.	CL_050_S_0300 -	
DESCRIZIONE / DESCRIPTION			
EASY LINE - CL 50 SINGLE ACTING STROKE 300			
ATTENTION! THIS DOCUMENT AND THE INFORMATION IT CONTAINS SHALL NOT BE REPRODUCED NOR DISCLOSED TO ANYBODY, BECAUSE PROPERTY OF CARIBONI S.r.l.			