


Function	Single acting cylinder - gas spring	
Bore	50	mm
Stroke	500	mm
Pull load @ 350 bar (max pressure)	6288	kg
Pull load @ 250 bar	4491	kg
Pull load @ 200 bar	3593	kg
Approx. dry weight	4,4	kg
Max oil volume	0,88	l

REV.	DATA / DATE	DESCRIZIONE / DESCRIPTION	NOME / NAME
RIFERIMENTO / REFERENCE			TABLE
TRAT. TERMICO / HEAT TREAT.			SIZE
CONTROLLATO / CHECKED			 <b>CARIBONI S.r.l.</b> Via Mattei 3/A 20885 Ronco Briantino e-mail: info@cariboni-italy.it www.cariboni-italy.com Tel +39 039 6079609 fax +39 039 6079128
AC			
APPROVATO / APPROVED			
DATA / DATE		30-11-2017	
SCALA / SCALE		1:3@A1	
PESO / WEIGHT		kg	
DISEGNO N. / DRAWING			
REV.			
CL_050_S_0500 -			
DESCRIZIONE / DESCRIPTION			
EASY LINE - CL 50 SINGLE ACTING STROKE 500			
ATTENTION! THIS DOCUMENT AND THE INFORMATION IT CONTAINS SHALL NOT BE REPRODUCED NOR DISCLOSED TO ANYBODY, BECAUSE PROPERTY OF CARIBONI S.r.l.			